

Features

- ✓ **Heat sink design** better for air convection, good heat dissipation, with Pre-Set color temperature button, Tri-color.
- ✓ **SMD LED**, up to 70 lm/W, CRI 80+.
- ✓ **Dimming capability**. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.






Specifications

Model	PRO-DL13CCTSM-D-GX
Voltage	AC200-240V 50/60Hz
Power	13W
LED	SMD LED
CCT	3000K-4000K-5000K
Flux	850lm-980lm-890lm
Efficiency	70lm/w
CRI	80+
Beam Angle	90°
Dimmable	Yes
IP Rated	IP44
Lifespan	>40,000Hrs
Cut-out	Ø90-120mm
Dimension	Ø125*H46mm
Warranty	3 years on driver, 5 years on downlight
Finish	White




Use the pre-set switch to set color temperature before installation.




Technical Data Test

90D-3000K


GO1900L GONIOPHOTOMETER Test Report




Light Source Test Report



SDCM: : 2.1 SDCM




Average Illuminance Figure




90D-4000K


GO1900L GONIOPHOTOMETER Test Report




Light Source Test Report



SDCM: : 4.8 SDCM




Average Illuminance Figure




90D-5000K


GO1900L GONIOPHOTOMETER Test Report



Light Source Test Report



SDCM: : 3.4 SDCM



Average Illuminance Figure

