



Features

- ✓ **Heat sink design** better for air convection, good heat dissipation.
- ✓ **SMD LED**, up to 85 lm/W, CRI 80+.
- ✓ **Dimming capability**. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.

Specifications


Model	DL06-09-A		
Voltage	AC200-240V 50Hz		
Power	9W		
LED	SMD LED		
Luminous Flux	2700K	625lm	67 lm/W
	3000K	710lm	77 lm/W
	4000K	775lm	83 lm/W
	5000K	780lm	85 lm/W
CRI	80+		
Beam Angle	90°		
Dimmable	Yes		
IP Rated	IP44		
Lifespan	>40,000Hrs		
Cut-out	Ø95-100mm		
Adjustable Angle	Adjustable 25°		
Dimension	Ø110*H41.5mm		
Inner Box	L138*W138*H90mm		
Carton	L57.5*W43*H29.5CM, 36pcs/CTN		
Warranty	3 years		




Technical Data Test

90D-2700K


001900L GONIOPHOTOMETER Test Report




Light Source Test Report



SDCM: : 2.9 SDCM




Average Illuminance Figure




90D-3000K


001900L GONIOPHOTOMETER Test Report




Light Source Test Report



SDCM: : 1.7 SDCM




Average Illuminance Figure




90D-4000K


001900L GONIOPHOTOMETER Test Report




Light Source Test Report



SDCM: : 0.4 SDCM




Average Illuminance Figure




90D-5000K


001900L GONIOPHOTOMETER Test Report



Light Source Test Report



SDCM: : 0.8 SDCM



Average Illuminance Figure

