

TECHNICAL DATA SHEET

Product Features: PRO-SERIES COMMERCIAL DOWNLIGHT

Pro-Series Downlight 282mm overall / 259-265mm cut-out / 60W Samsung

Pro-Series Commercial is a family of recessed downlight, the Ideal solution for space lighting application, extremely low power consumption means significant energy savings compared with traditional CFL downlights.

Not only that — they deliver excellent light performance, with high lumens flux, very good colour rendering, Triac dimming, and so on.

In additional, they offers a wide choice of sizes and accessories to ensure maximum flexibility in application. These innovative downlights can be used in environments requiring a green general-lighting solution, for instance in offices, shops, malls, hotels and hospitals.

IP20 and IP44 available for various applications.

Model: PRO-DLR60PW



LED	Samsung LM-80-08 TM-21-11
Driver option	Tridonic driver
Input Voltage	AC90-265V 50~60Hz
Power factor	>0.90
Lamp / Driver Consumption	60W
Color temperature	3000K / 4000K / 5000K / 6000K
Luminous Flux	3000K=5700lm 4000K=6000lm 5000K=6300lm 6000k=6100lm
CRI	Ra>82
Beam angle	90° Frosted Lens
External dimension	D: 282mm X H: 130mm Cut-out: 259-265mm
Warranty	5 Years
Wire connection and Plug	Australia: SAA 3 X 0.75mm2 Plug Europe: 3 X 0.75mm2 Cable
Certificates	CE SAA C-tick TUV RoHS LM-80-08 TM-21-11



