

TECHNICAL DATA SHEET


PRO-SERIES LED DECK & INGROUND LIGHT SERIES

316 Stainless Steel IP68


- IP68 Stainless Steel 316 ideal for use in external harsh environments including decks, stairs, gardens, floors, decorative features, recreational facilities, parks and other outdoor areas
- No flicker or RF interference, no buzzing noise, instant soft start and low heat
- Colour options of white, warm white, amber, red, blue, green, RGB
- High power LED waterproof with excellent performance, high temperature resistance, anti-aging and corrosion resistant with long life up to 50,000 hours
















LED Beam angle CCT(K)

Materia

CREE/ LG/ Epistar

2700K-6500K,RGB single color,

RGB 3 in 1

80

Ra AC/DC12V DC24V Voltage (V)

SS316

Power (W) 0.6W Luminous flux (lm) 36 lm ¢ 30*27 Size(DxH)(mm)

IP Grade IP68

Beam angle

LED

Ra

CCT(K)

Voltage (V)

Power (W) Luminous flux (lm)

Size(DxH)(mm)

Material IP Grade CREE/LG/Epistar

2700K-6500K RGB single color,

RGB 3 in 1

80

AC/DC12V DC24V

1W

56 m ¢35*25 SS316

IP68

LED

Beam angle

CCT(K)

Ra

Voltage (V) Power (W)

Luminous flux (Im)

Size(DxH)(mm) Material IP Grade

CREE

15°, 25°, 40°, 60°, 120°

2700K-6500K RGB single color,

RGB 3 in 1

80

AC/DC12V DC24V 1.5-2W

130**l**m

IP68

⊄45*40 SS316

