


Features

- ✓ Polycarbonate body.
- ✓ High efficiency, up to 75lm/W.
- ✓ Pre-set tri-color-temperature switch for diverse needs.
- ✓ External driver and dimming capability suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.






Specifications

Model	PRO-DL10CCTSM-D-LX
Voltage	AC200-240V 50/60Hz
Power	10W
LED	SMD LED
CCT	3000K-4000K-5000K
Flux	650lm-800lm-700lm
Efficiency	75lm/w
CRI	80+
Beam Angle	90°
Dimmable	Yes
IP Rated	IP44
Lifespan	>40,000Hrs
Cut-out	Ø90-135mm
Dimension	Ø140*H57mm
Warranty	3 years on driver, 5 years on downlight
Finish	White




Use the pre-set switch to set color temperature before installation.



Technical Data Test


90D-3000K

GO1900L GONIOPHOTOMETER Test Report




C Plane [3000K] [100lm/W] [100lm/W]
 CRI: 80.0, 80.0, 80.0, 80.0, 80.0, 80.0
 CRI: 80.0, 80.0, 80.0, 80.0, 80.0, 80.0

Light Source Test Report




x=0.440 y=0.403 F3000

SDCM: : 5.9 SDCM




Average Illuminance Figure




90D-4000K

GO1900L GONIOPHOTOMETER Test Report




C Plane [4000K] [100lm/W] [100lm/W]
 CRI: 80.0, 80.0, 80.0, 80.0, 80.0, 80.0
 CRI: 80.0, 80.0, 80.0, 80.0, 80.0, 80.0

Light Source Test Report




x=0.380 y=0.380 F4000

SDCM: : 4.8 SDCM




Average Illuminance Figure




90D-5000K

GO1900L GONIOPHOTOMETER Test Report




C Plane [5000K] [100lm/W] [100lm/W]
 CRI: 80.0, 80.0, 80.0, 80.0, 80.0, 80.0
 CRI: 80.0, 80.0, 80.0, 80.0, 80.0, 80.0

Light Source Test Report



x=0.340 y=0.359 F5000

SDCM: : 5.2 SDCM



Average Illuminance Figure

