


Features

- ✓ **Heat sink design** better for air convection, good heat dissipation.
- ✓ **SMD LED**, up to 78 lm/W, CRI 80+.
- ✓ **Dimming capability**. Suits triac dimmers including OPUS, Clipsal, HPM, Niko, Lumeo Domus, Lumeo Eco. The driver with SAA, RCM and CE certification.



Specifications


Model	DL08-10	
Voltage	AC200-240V 50Hz	
Power	10W	
LED	SMD LED	
Luminous Flux	3000K	670lm
	4000K	710lm
Efficiency	75 lm/W-78 lm/W(3000K-4000K)	
CRI	80+	
Beam Angle	90°	
Dimmable	Yes	
IP Rated	IP40	
Lifespan	>40,000Hrs	
Cut-out	Ø70-75mm	
Dimension	Ø90*H38mm	
Packaging	L115*W115*H105mm	
Carton	L59.5*W36.5*H23.5CM, 30pcs/CTN	
Warranty	3 years	




Technical Data Test

90D-3000K


GO1900L GONIOPHOTOMETER Test Report




Light Source Test Report



SDCM : 1.1 SDCM




Average Illuminance Figure




90D-4000K


GO1900L GONIOPHOTOMETER Test Report



Light Source Test Report



SDCM : 0.4 SDCM



Average Illuminance Figure

